## BetaScreen® 20





<b>Product Data</b>	1%	3%
Composition	Glass fibre 36%, PVC 64	%
Width	1600 mm, 2500 mm	1600mm, 2500mm, 3200mm
Thickness	0.6 mm	0.55 mm
Weight	465 gsm	470 gsm
Openness factor	1%	3%
Fire rating	BS5867 Part 2 Type B	
Cleaning	Soapy water	

## **Thermal Control Values**

	1%					3%				
Colour	Code	Tv	Ts	Rs	As	Code	Tv	Ts	Rs	As
White/Charcoal	BS20111	3%	3%	43%	54%	BS20113	6%	6%	45%	49%
White/Grey	BS20211	3%	4%	48%	48%	BS20213	7%	8%	49%	43%
White/Pearl Grey	BS20311	7%	9%	55%	36%	BS20313	10%	12%	55%	33%
White/White	BS20411	18%	19%	66%	15%	BS20413	20%	21%	66%	13%

Glare control Tv = % of visible light transmitted through fabric

Thermal control As = % of solar energy absorbed by fabric

Rs = % of solar energy reflected by fabric

Ts = % of solar energy transmitted through fabric


## **Properties**



Visual comfort Flame retardant

Through visibility Easy to clean

**Tear resistance** Fabric can be joined




For further information, contact us on 01252 737973 or visit www.waverley.co.uk

Visit www.waverley.co.uk for further technical information











White / Charcoal

White / Grey

White / Pearl Grey

White / White

For further information, contact us on 01252 737973 or visit www.waverley.co.uk

