


NAXOS III

Transparent, mesh like curtain fabric in Trevira CS. The 300 cm wide leno weave captivates with a technology inspired look and a delicate and elegant sheen. The fascinating changeant effect derives from the use of contrast rich colours in warp and weft. Naxos III is ideal for use in both residential and contract sector furnishing. It is now available in 29 colours.



Use:	Transparent curtain fabric
Number of colours:	29 Special colours available from 300 m / 330 yds upwards.
Material:	100% Flameretardant polyester (Trevira CS)
Fabric width:	300 cm/118 inch/3.28 yard
Can be railroaded:	Can be railroaded
Weight:	67 g/m ²
Flame-retardant properties:	
Additional use:	  
Care:	    
Washing (length shrinkage):	1%
Dry cleaning (length shrinkage):	1%
Certificates / tests:	Fire Test DIN 4102 B1 Brenntest SNV 198898 Fire Test Japan Fire Test M1 Lightfastness certificate IMO Curtains

*all testing reports can be downloaded from our website under product details



NAXOS III



Col. 0204



Col. 0205



Col. 0207



Col. 0301



Col. 0302



Col. 0303



Col. 0304



Col. 0305



Col. 0306



Col. 0307



Col. 0308



Col. 0309



Col. 0310



Col. 0311



Col. 0312



Col. 0313



Col. 0314



Col. 0315



Col. 0316



Col. 0317




Col. 0318



Col. 0319



Col. 0320



Col. 0321



Col. 0322



Col. 0323



Col. 0324



Col. 0325



Col. 0326

Note:

Colours may vary. Please ask for our colour samples.

* As long as stock lasts

CARE SYMBOLS FOR TEXTILES

Washing (wash tub)

	Normal process 95°
	Mild process 95°
	Normal process 60°
	Mild process 60°
	Normal process 40°
	Mild process 40°
	Very mild process 30°
	Hand wash
	Do not wash

The numbers in the washing tub specify the maximum temperature in °C which must not be exceeded. The bar underneath the wash tub characterizes a milder cycle with reduced mechanical action.

Ironing (hand iron)

	Iron at maximum sole-plate temperature
	Iron at a medium sole-plate temperature. Take care when using a steam iron
	Iron at a low sole-plate temperature. Take care when using a steam iron
	Do not iron

The number of dots indicates the severity as regards to temperature of the handiron.

Chlorine-based bleaching (triangle)

	Chlorine-based bleaching allowed
	Do not use chlorine-based bleach

Tumble drying (circle in a square)

	Drying at a lower temperature setting
	Do not tumble dry

The numbers of dots indicates the severity as regards to temperature of the tumble drying treatment.

Dry-cleaning (circle)

	Self-service cleaning also allowed (A)
	Drycleanable
	Drycleanable
	Self-service cleaning not allowed (F)
	Self-service cleaning not allowed (F2)
	Do not dry clean
	Mild professional wet-cleaning

The letters within the circle specify the solvents that can be used. The bar under the circle indicates that certain limitations in the drycleaning process are required. These may concern mechanical action and/or drying temperature and/or water addition in the solvent. – No selfservice cleaning allowed.

Gecko

	Cleaning with window wiper (Unger method)
	Cleaning by "Spray Extraction" method by machine

SYMBOLS AND PRODUCT INFORMATION

Product information

	Inherently flame retardant
	Width (cm)
	Can be railroaded
	Has to be railroaded
	Must not be railroaded
	Pattern repeat displaced
	Repeat in warp direction
	Repeat in weft direction
	Weight (g/m2)
	Yarn dyed
	Piece dyed
	Knitted
	Woven
	Warp print
	Screen print/burnout
	Metalized on one side

	Free from harmful substances / Oddy
	Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.)
	light transmission level Tv, n-h
	light transmission level Tv, n-nn
	light transmission level Tv, n-dif
	light reflection level Pv, n-h
	light absorption level Av
	UV transmission level Tuv
	solar transmission level Te, n-h
	solar reflection level Pe, n-h
	solar absorption level Ae

Material information

AC	Acetate
CA	Hemp
CO	Cotton
EA	Elasthan
GL	Glass fibre
LI	Linen
MD	Modal
ME	Metal
PA	Polyamide
PC	Acrylic
PE	Polyethylene
PI	Paper
PL	Polyester
PLF	Flameretardant polyester
PLF CS	Flameretardant polyester (Trevira CS)
PN	Polycarbonat
PP	Polypropylene
PU	Polyurethan
RA	Ramie
SE	Silk
SI	Silicone
TR	Different material (wood, paper, feathers etc.)
VI	Viscose
WM	Wool Mohair
WV	Wool

SYMBOLS AND PRODUCT INFORMATION

Intended purposes



Curtains/Sheers



Roller blinds (colours see separate roller blind collection)



Panels (we recommend to process the panels in warp direction to get optimal hang properties)



Vertical blinds



Roman blinds



Upholstery (for heavy use in contract application).
Martindale > 30'000



Upholstery (for heavy use in domestic application/for normal use in contract application). 20'000 < Martindale < 30'000



Upholstery (for normal use in domestic application/for careful use in contract application). Martindale < 20'000



Loose cover for careful use in domestic application.
Martindale < 5'000



Bedspreads



Table cloth domestic use



Wallcovering



Textile wallpaper (can be paper backed, minimum quantity)



Cushion



Acoustical fabrics



Adhesive Textiles/Gecko/Gecko in the Box



Fabrics with very high lightfastness for indoor and outdoor use



Reverso