

dolin

8048.01 - 8048.09



binder

curtain 01

description

light textured blend

composition

100% flame retardant polyester

width

± 140 cm, ± 55 inches

weight

± 407 gr/m¹, ± 13 oz/yd¹ fabrics

visual & thermal comfort

EN 410/EN 14501

flame retardancy

EN 13773, class 1

BS 5867-2, type C

NF P 92/503-507, M1

DIN 4102, B1

UNI VF 8456-8457, classe 1

IMO 2010 FTP part 7

NFPA 701

CAN ULC S109

colorfastness to crocking

ISO 105-X12

wet 4-5 / dry 4-5 (scale 1-5)

AATCC 8

wet 5 / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02

6 (scale 1-8)

AATCC 16.3: 60 hrs

5 (scale 1-5)

seam slippage

ISO 13936-2

warp 5.5 mm / weft 4.7 mm

ASTM D434

warp 32 lbs / weft 30 lbs

care



shrinkage: warp -2% / weft -1%



shrinkage: warp -2.8% / weft -2%



dolin


8048.01 - 8048.09



8048.01



8048.02



8048.03




8048.04




8048.05



8048.06



8048.07



8048.08



8048.09