



## Configuration settings

Feature	Value
Configurations from the sun shading planner are not full orders! The online platform myWAREMA is available for this purpose!	
front-mounted roller shutter	V6 – standard box (extruded)
box shape	rectangular (E)
installation	in the soffit
configuration individual Unit	
max. operating forces	due to design
supplementary accessory	none
Wind resistance class	0
shutter curtain profile	A 37
box version	four-sided
insect screen	without (standard)
execution of mounting	Left rolling blind
Guide rail	FSCH 55-25
sealing strip in the guide rail	sealing strip (standard)
sealing cord	without
Guide rail insulation	without
Drive	Motor with torque overload protection
Drive end (as seen from the inside)	right
section to receive plastering	without
Ordering width (mm)	1200
Ordering height (mm)	1200
sealing strip in the bottom rail	without
box size	control mode
Note	
limit values (individual Unit)	
Maximum width	3000 mm
maximum height	3500 mm
maximum surface (individual Unit)	7.0 m <sup>2</sup>
Maximum surface insect screen	-
calculations and results	
actual box size:	130
actual element surface:	1.44 m <sup>2</sup>
wind resistance category entered:	
0	
wind resistance category actually achieved:	
0	
shutter curtain weight in kg	
3.89	
notes	
- box:	closed at 4 sides
- mitre cuts:	possible

Feature	Value
- coupled Units (max. 3 curtains):	Per coupling, 10% of the curtain surface must be added for friction!
Display options	
Display	selective selection
dimension	fade in
mounting situation	fade in
insertion point	fade in
Selection of views	all views

#### WAREMA Renkhoff SE

Hans-Wilhelm-Renkhoff-Straße 2, D-97828 Marktheidenfeld

Telefon: 09391 / 20-0

Telefax: 09391 / 20-42 99

E-Mail: [info@warema.de](mailto:info@warema.de)

Internet: <http://www.warema.de>

